



This information corresponds to our current knowledge on the subject. It is offered solely to provide possible suggestions for your own experimentation. It is not intended, however, to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes. This information may be subject to revision as new knowledge becomes available. Since we cannot anticipate all variations in actual end use conditions, Geosynthetic Limited makes no warranties and assumes no liabilities in connection with this information. Nothing in this publication is to be considered as a licence to operate under or a recommendation to infringe any patent right.




FIGURE 6: PIN PATTERN DETAIL




FIGURE 7: SIMULATED CHECK SLOT DETAIL




FIGURE 9: PIN DETAIL




FIGURE 8: TERMINAL TRENCH AT TOE OF SLOPE DETAIL




FIGURE 10: EARTH PERCUSSION ANCHOR DETAIL

ARMORMAX™ SYSTEM ON A SLOPE (NON-STRUCTURAL APPLICATION)

PRE CONSTRUCTION

- A pre-construction meeting should be held with the construction team and a representative from Geosynthetic Limited. This meeting shall be scheduled by the contractor with at least two weeks notice. Also, Geosynthetic Limited suggests that installation monitoring of the ArmorMax™ System be performed by a qualified independent third party.

SITE PREPARATION

- Grade and compact area of ArmorMax™ installation as directed and approved by Engineer. Subgrade shall be uniform and smooth. Remove all rocks, loose soil and clay, vegetation or other objects so the installed mat will have direct contact with the soil surface.
- Prepare seedbed by loosening the top 50-75mm minimum of soil.
- Incorporate amendments such as lime and fertiliser and/or wet the soil, if needed.
- Do not mulch areas where mat is to be placed.

SEEDING

- Apply seed to soil surface before installing mat. Disturbed areas shall be reseeded.
- Consult project plans and/or specifications for seed types and application rates.

INSTALLATION ON A SLOPE

- Figure 1 shows general installation layout and details for ArmorMax™ System on a slope.
- Excavate initial trench 300mm wide x 300mm deep minimum 600-900mm over crest of slope (see Figure 2).
- Excavate longitudinal edge trenches 300mm x 300mm minimum along both sides of the installation to bury edges of mat (see Figure 3). The longitudinal edge trenches shall be located along the first and last installed rolls.
- Beginning at the downstream end of prevailing winds, place roll end into the initial trench and secure with pinning devices on 300mm centers and with earth percussion anchors on 1.2m centers (see Figures 2). Position adjacent rolls and secure in trench in same manner. Backfill and compact soil into trench as directed and approved by Engineer.
- Unroll mat down the slope over the compacted initial trench.
- Secure longitudinal edge trench with pinning devices on 300mm centers and with earth percussion anchors on 1.2m centers (see Figure 3).
- Continue installation as described above, overlapping adjacent rolls as follows:
 - Roll edge overlap -150mm minimum overlap with upstream mat on top. Secure with one row of ground pinning devices on 300mm centers and with one row of earth percussion anchors on 1.2m centers (see Figure 4)
 - Roll end overlap: 300mm minimum overlap with upslope mat on top. Secure with two rows of ground pinning devices staggered 300mm apart on 300mm centers and with one row of earth percussion anchors on 1.2m centers (see Figure 5)
- Secure mat using suggested ground pinning devices and earth percussion anchors for appropriate frequency and pattern shown on the Anchor/Pin Pattern Detail (see Figure 4) and Pin/Pattern Detail (see Figure 6)
- For slope heights greater than 13.7m, install simulated check slots per Figure 7. This method included placing two staggered rows of pins 100mm centers on 100mm centers and one row of earth percussion anchors on 1.2m centers at 9.1m intervals (see Figure 7) or across the midpoint of the slope height for slope heights less than 18.2m.
- Excavate terminal trench 300mm wide x 300mm deep, minimum 300mm from the toe of the slope (see Figure 8).
- Pin, backfill and compact end of mat in terminal trench (see Figure 8). Terminal trench pinning devices should be spaced on 300mm centers and earth percussion anchors on 1.2m centers (see Figure 8).

GROUND PINNING DEVICES

- Metal pins should be at least 5mm diameter steel with a 38mm steel washer at the head of the pin (see Figure 9). Metal pins should be driven flush to the soil surface. Pins should be between 150-600mm long and have sufficient ground penetration to resist pullout. Longer pins may be required for looser soils. Heavier metal stakes may be required in rocky soils. Depending on soil pH and design life of the pin, galvanised or stainless steel pins may be required. Consult project plans and/or specifications for tie down device details.
- Earth Percussion anchors are made of corrosion resistant aluminium alloy, gravity die cast and heat treated to give considerable increase in mechanical strength and durability both during installation and in service, connected to a stainless steel tendon to fully enhance corrosion resistance particularly at the soil/air interface. Non-structural applications are typically designed using Type 2 earth percussion anchors. Earth percussion anchor length, anchor size, and washer width shall be determined and approved by Engineer (see Figure 10).

SPECIAL TRANSITIONS

- For applications that require special transitions (i.e. connections to riprap, concrete, headwalls, etc).

SOIL FILLING

- Installed Pyramat® HPTRM shall be re-seeded and soil-filled.
- After seeding, spread and lightly rake 12-19mm of fine site soil or topsoil into the mat and completely fill and voids using backside of rake or other flat tool.
- If equipment must operate on the mat, make sure it is of the rubber-tired type. No tracked equipment or sharp turns are allowed on the mat.
- Avoid any traffic over the mat if loose or wet soil conditions exist.
- Smooth soil-fill in order to just expose the top of Pyramat® HPTRM. Do not place excessive soil above the mat.
- Broadcast additional seed and install a Landlok® ECB above the soil-filled mat (if desired).
- Irrigate as necessary to establish/maintain vegetation. Do not over irrigate.