

Alert™

Alert™ Woven Polypropylene Geotextile and Contamination Indicator

Alert™ was developed by Geosynthetics Limited to provide a cost effective and practical way to indicate the break between potentially contaminated ground and imported or site won clean fill. The large roll size combined with industrial leading technical specifications and strength have lead to the vivid orange **Alert™** woven geotextile being the product of choice in the UK.



PROPERTY	TEST METHOD	Value
Colour		Orange
Tensile strength - warp	BS EN ISO 10319	18 kN/m
Tensile strength - weft	BS EN ISO 10319	12 kN/m
Elongation at break - warp	BS EN ISO 10319	28 %
Elongation at break - weft	BS EN ISO 10319	16 %
CBR puncture resistance	BS EN ISO 102236	1840 N
Water flow normal to the plane	BS 6906 Part 3	32 l/m ² /sec
Pore size 90% finer than	BS 6906 Part 2	230 microns
Effects of UV light		The polypropylene used contains a UV inhibitor
Fabric thickness under 2 kN/m ²		0.39 mm
Standard roll width		4.5 m
Standard roll length		100 m
Applications		Brownfield sites Developed land Warning indicator
CE Reference		0338-CPR-5058

This information corresponds to our current knowledge on the subject. It is offered solely to provide possible suggestions for your own experimentation. It is not intended, however, to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes. This information may be subject to revision as new knowledge becomes available. Since we cannot anticipate all variations in actual end use conditions, Geosynthetics Limited makes no warranties and assumes no liabilities in connection with this information. Nothing in this publication is to be considered as a licence to operate under or a recommendation to infringe any patent right.

DR: 04/V2/29.10.15

**UK
CA**
**Geosynthetics**